Command Tubular Products

Command Extended Wear™



Command Extended Wear™ vs. Standard Drill Pipe

- Reinforces high-wear areas to enhance tube durability and longevity
- Extends pipe lifespan while lowering overall cost of ownership with fewer maintenance needs
- Improves weight transfer to the drill bit and increasing rate of penetration (ROP)
- Minimizes buckling, drag and friction for smoother operations
- Engineered and manufactured to be run in the toughest horizontal drilling environments

Maximize Your Drilling Performance

Combine **Command Enhanced Torque® (CET®)** and **Command Extended Wear™ (CEW™)** to achieve superior drilling efficiency and performance

CANADA	EUROPE	AUSTRALASIA	USA	MIDDLE EAST
406 - 22nd Ave Nisku, Alberta **780 955-9331**	5 rue des Guerins 58200 Cosne sur Loire, France **+33 6 87 99 90 14**	AB0801, JAFZA One B, Jebel Ali Freezone, Dubai, UAE **+971 58 836-6520**	18911 West Industrial Pkwy New Caney, TX 77357 **281 572-3900**	Street 117, 2nd Industrial City, Dammam, Saudi Arabia **+966 50 481-1416**



Leading worldwide manufacturer of drill pipe and drill stem accessories

www.commandtubular.com

Command Extended Wear™



CEW™

Key Benefits

- **Superior Durability** – Strengthened high-wear areas minimize fatigue and extend service life
- **Lower Cost of Ownership** – Enhanced longevity reduces the need for frequent replacements
- **Optimized Drilling Efficiency** – Improved energy transfer to the bit increases ROP
- **Reduced Downtime** – Greater wear resistance means fewer operational interruptions
- **Reliable Performance** – Engineered for high-demand drilling environments

Standard CET® TJ Lengths

13” Pin x 16” Box

Standard CWP Length

30”

Sizes and Make-up Torque

Connection	Nominal Tube Size	Nominal Wall Thickness	Center Wear Pad OD	Center Wear Pad Wall Thickness	Tool Joint OD	Tool Joint ID	Recommended MUT
CET®39	4” 14.0#	.330”	4 3/8”	**.518”**	4 7/8”	2 11/16”	**22,200 ft.lbs**
	4” 15.7#	.380”		**.568”**			
CET®43	4 1/2” 16.6#	.337”	4 7/8”	**.525”**	5 3/8”	3”	**31,700 ft.lbs**
	4 1/2” 20.0#	.430”		**.618”**			
CET®45	5” 19.5#	.362”	5 3/8”	**.550”**	5 7/8”	3 1/4”	**42,800 ft.lbs**
	5” 25.6#	.500”		**.688”**			
CET®50	5” 19.5#	.362”	5 3/8”	**.550”**	6 5/8”	3 3/4”	**48,400 ft.lbs**
	5” 25.6#	.500”		**.688”**			
CET®54	5 1/2” 21.9#	.361”	5 7/8”	**.549”**	6 5/8”	4”	**52,600 ft.lbs**
	5 1/2” 24.7#	.415”		**.603”**			

Standard drill pipe grades: 105 – 150 ksi minimum yield strength (G-105 to V-150). Other grades available on request.

Combine **Command Enhanced Torque® (CET®)** and **Command Extended Wear™ (CEW™)** to achieve superior drilling efficiency and performance